6

We claim

- A catalyst for heterogeneously catalyzed reactions, which comprises active components and a catalyst support comprising amounts of $\delta\text{-Al}_2\text{O}_3$ which can be detected by X-ray diffractometry.
- A catalyst for heterogeneously catalyzed reactions as claimed in claim 1, wherein the catalyst support comprises 10 from 10 to 100% by weight of δ -Al₂O₃.
- 3. A catalyst for heterogeneously catalyzed reactions as claimed in either of claims 1 and 2, wherein the active components employed are from 1 to 15% by weight of copper, 15 from 0.1 to 6% by weight of alkali metals, from 0 to 5% by weight of alkaline earth metals, rare-earth metals or mixtures thereof.
- 20 4. A catalyst for heterogeneously catalyzed reactions as claimed in claim 1, prepared by impregnating a shaped δ -Al₂O₃-containing support having a BET surface area of from 80 to 250 g/m² with salts of copper, alkali metals and, if desired, alkaline earth metals, rare-earth metals or mixtures thereof. 25
 - 5. A process for the preparation of a catalyst for heterogeneously catalyzed reactions as claimed in one of claims 1 to 3, which comprises impregnating the
- $\delta-Al_2O_3$ -containing support with salts of copper, alkali 30 metals and, if desired, alkaline earth metals, rare-earth metals or mixtures thereof, separately from one another or together, if desired with the addition of acids or oxidants.
- A process for the preparation of a catalyst for heterogeneously catalyzed reactions as claimed in claim 5, wherein the salts employed are chlorides.
- The use of a catalyst for heterogeneously catalyzed reactions as claimed in one of claims 1 to 4 for exothermic 40 gas-phase reactions.
- 8. The use of a catalyst for heterogeneously catalyzed reactions as claimed in one of claims 1 to 4 for 45 oxychlorination reactions.

7

- 9. The use of a catalyst for heterogeneously catalyzed reactions as claimed in one of claims 1 to 4 for the oxychlorination of ethylene to 1,2-dichloroethane.
- 5 10. A process for the preparation of 1,2-dichloroethane, which comprises reacting ethylene with hydrogen chloride and air or oxygen in the presence of a catalyst as claimed in one of claims 1 to 4 at a temperature of from 150 to 400°C and a pressure of from 1 to 10 bar.
 - 11. The use of a catalyst for heterogeneously catalyzed reactions as claimed in one of claims 1 to 4 for partial oxidation reactions.

15

10

20

25

30

35

40

45